


**END-OF-LINE DEFLAGRATION FLAME ARRESTER**

**Typ: DAG-A7K-C-IIC-025**

Certificate: IBExU11ATEX2167 X EN ISO 16852 

<b>PIPE CONNECTION</b>		
<b>FLANGED CONNECTION</b>	DN 25 - DIN 2631 - PN6*	
* According to the customers' request DIN 2632 PN10 or DIN 2633 PN16		
<b>THREAD CONNECTION</b>	DN 25 - 1"	
<b>MATERIAL OF CASING, CONNECTING FLANGES AND CONNECTION MATERIAL</b>		
ČSN 11 373	DIN 1.0036	S235JRG1
ČSN 17 240	DIN 1.4301	X5CrNi18-10
ČSN 17 348	DIN 1.4571	X6CrNiMoTi17-12-2

<b>MATERIAL QUENCHING ELEMENT</b>	DIN 1.4571 - X6CrNiMoTi17-12-2
<b>SEALING</b>	CS1310 th. 2 mm (expanded graphite)
<b>CORROSION PROTECTION</b>	Zink, Komaxit RAL 2004
<b>ARRESTER WEIGHT</b>	ca. 3,5 kg
<b>OPERATING TEMPERATURE RANGE</b>	-20 °C... +60 °C
<b>NAMEPLATE</b>	stainless metal sheet
<b>EXPLOSION CLASS</b>	<b>IIC</b>



SafExty NExus®



ROZMĚRY - ABMESSUNGEN DIMENSIONS		
D	DN	25
E	[mm]	100
F	[mm]	120
L	[mm]	100
L1	[mm]	34
L2	[mm]	95
L3	[mm]	16
FL	DIN 2631	PN6
G"	[inch]	1"

Technické změny vyhrazeny -  
Technische Änderungen vorbehalten -  
Specifications subject to change without notice

